

GWIR-030M



Features:

- * Uncompressed and no-delay
- * Support HDMI single wireless transmission up to 30 meters
- * 30M HDMI wireless Transmission
- * Resolution: 480i,576i,720p,1080i,1080p 24/30/50/60
- * Audio :PCM,ACC,Dolby digital 2.0/5.1 DTS5.1 ,LPCM5.1/7.1
- * Graphics Modes: Full HD
- * Maximum Video Resolution: 1920 x 1080
- * Mini USB: in/out
- * HDMI: in/out

Specification	GWIR-030M
Model	HDMI Wireless Extender
TX interface	HDMI in, DC in, Scan button, mini USB, LED indicator
RX interface	HDMI out , DC in,, Scan button, mini USB, LED indicator
HDMI format	2D:480I/P,576I/P,720P,1080I,1080P 3D:720P,1080P PC :WVGA (848X480),SVGA(800X600), XGA (1024X768), SXGA (1280X1024)
HDMI protocol	HDMI1.3, HDMI1.4 3D, HDCP2.0
Audio format	S/PDIF, AAC, Dolby Digital2/7.1, DTS5.1,LPCM5.1/7.1
Latency	<1ms
Frequency	HRP2:59.40--61.56Ghz, HRP3:61.56-63.72Ghz
Bandwidth	1.76Ghz
Transmitting power	28dbm
Antenna gain	18dbi
Antenna angle	-80 degree ~ 80degree
Receiver sensitivity	-72dbm
Noise figure	11db
Distance	30 meters line of sight
Power supply	DC5V,1A
Power consumption	3.3W
Dimension	89.5 X 34.5 X 20mm

Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com