

VCF-1008DA-P



Features

- * SD/HD/3G-SDI 1 to 8 Distribution Amplifier
- * SD-SDI (270Mbps), HD-SDI (1.485Gbps), 3G-SDI (2.97Gbps)
- * Built-in Cable Equalizer, Re-clocker & Cable Driver
- * Max. cable length : SD-SDI 400M/1300ft, HD-SDI 200M/600ft, 3G-SDI 60M/450ft
- * Excellent SDI signal jitter suppression function
- * Power supply and SDI signal format indicator
- * Embedded ESD to protect the circuit
- * Audio Support

Specification	VCF-1008DA-P
MODEL	1CH Input 8CH Output SDI Signal Distribution Amplifier
Signal Input	1 x BNC (75 Ohm, SDI)
Signal Output	8 X BNC (75 Ohm, SDI)
Video Bandwidth	SD-SDI (270Mbps), HD-SDI (1.485Gbps), 3G-SDI(2.97Gbps)
Input Format	SD-SDI: 525i@ 59.94Hz, 625i@50Hz HD-SDI: 720p@23.98Hz/24Hz/25Hz/29.97Hz/30Hz@50Hz/59.94Hz/60Hz 1080i@:50Hz/59.94Hz/60Hz1080p@23.98Hz/24Hz/25Hz/29Hz/30Hz 3G-SDI: 1080p@ 50Hz/ 59.94Hz/ 60Hz
SDI Signal Range	0.8V p-p
SDI Impedance	75 ohms
Max. Distance	Belden 1694A SD-SDI 400M / 1300ft ; HD-SDI 200M / 600ft ; 3G-SDI 140M / 450ft
Power Supply	5V~24V DC
Operating Temperature Range	-10°C ~ + 55°C
Storage Temperature Range	-20°C ~ + 60°C
Operating Humidity Range	10 ~ 90%RH (No Condensation)
Storage Humidity Range	5 ~ 95%RH (No Condensation)
Dimension (I X W X H)	120 x 57 x 36 mm / 4.72 x 2.24 x 1.42 inches
Weight	300g



Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com