

VCF-FB08TX/RX

IP Surveillance
EquipmentHD-SDI / 3G-SDI
EquipmentAHD / TVI / CVI
EquipmentHDMI / VGA
Equipment

Speed Dome Camera

Matrix Switcher Solutions



Features

- * Comply with SMPTE-292M HD-SDI standard
- * 1080P@30,25,24, 1080I@60,50 and 720P@60,50,30,25,24
- * With integrated cable equalizer
- * Embedded ESD and surge protection circuit to prevent damage from static and thunder
- * AUX function : only Audio signal choice or alarm signal choice but nor both choice
- * With NOP (No optical signal) alarm indications, output status indicator and input lock indicator
- * With APC circuit to perform stable optical power

Specification	VCF-FB08TX/RX
Model	Mini version 4CH HD-SDI Video and Audio fiber extender
Input	8CH BNC (75ohm, SDI)
SignalType	SD-SDI (270Mbps) / HD-SDI (1.485Gbps)
Support Input Format	SD:525i@59.94Hz,625i@50Hz HD:1080P@30,25,24,1080I@60,50and 720P@60,50,30,25,24
Video Standard	SMPTE292M and SMPTE259M
In-outelectrical Level	800mVp-p±10%
Audio	Integrated SDI signal
Digital Audio	48KHz
AES Digital Audio Channel	8CH
Fiber interface	FC/PC (SC to custom)
Fiber type	Single Mode,Single Fiber
Wave length	1310/1550nm
Max.Distance	0m-20Km
Transmitted Power	-5dbm~-10dbm
Maximum Receiving Sensitivity	-28dBm
DATAcomm.method	RS-485/Halfduplex
Power Supply	AC 100-260V
Power Consumption	3~5Watts
Operating Temperature	0°C~60°C/ 32°F~140°F
StorageTemperature	-30°C~70°C/ -22°F~158°F
Relative Humidity	20~90%RH (Non-condensation)
Dimension	19in,1Utall,155mm wide
Weight	5000 g (TX and RX)



Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com