

DVR7016-SDI



Features

- * 16CH HD-SDI 480fps,1080p Recording
- * 4ch audio input & 1ch audio output
- * HDMI,VGA output up to 1080P
- * RS485*1
- * SATA*2 to 16TB
- * USB*3,RJ45*1(1000M)*1
- * HD-SDI Resolution Support :
1080P/30,25Hz

Specification	DVR7016-SDI
System	
Main Processor	High performance Dual-core embedded microprocessor
Operating System	Embedded LINUX
System Resources	Pentaplex function: live, recording, playback, backup & remote access
Control Mode	Front panel, USB mouse, Networ
Video	
Input	16 channel (HD-SDI), BNC
Standard	1080P
Output	*1 HDMI,*1 VGA
Audio	
Input	4 channel
Output	1 channel
Display	
Display Split	1/4/9/16
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Tour Display	Supported
OSD	Camera title, time, video loss, camera lock, motion detection, recording
Recording	
Video Compression	H.264
Recording Resolution	1080P(1920×1080)
Recording Speed	1080P
Recording Mode	Manual, Schedule, Regular(Continuous), Video detection: Motion detection
Video Detection & Alarm	
Triggered Events	Recording, PTZ movement, Tour, Email, FTP, Buzzer & Screen tips
Motion Detection	Supported
Video Loss	Supported
Playback & Backup	
Search Mode	Time / Date
Backup Mode	Flash drive / Network download
Network	
Ethernet	RJ-45 port (10/100M/1000M)
Network Functions	HTTP, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE,DDNS, FTP
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information
Hard Disk	SATA*2 to 8TB(each HDD), totally up to 16TB
Auxiliary Interface	
USB Interface	3 USB2.0 ports, For mouse control & backup
RS485	PTZ control
Environmental	
Power Supply	DC12V/4A
Working Environment	-10 ~+55°C/ 10~90%RH / 86~106kpa
Weight	5KG(without HDD)

Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com