

ACT-FB01TXRX

Description Features:

- * Support AHD/CVI/TVI/Analog all Signal
- * Support resolution: 1080p, 720p, 960H, D1, all in one
- * Compatible with NTSC、PAL、SECAM video formats automatically
- * Supports RS485/Manchester Code/Diphase data, Switching signal
- * FC Type, Single mode, single fiber
- * Compact structure, easily installation, plug and play
- * Overpower protection and 5.7KV proof-lightning



Model No.	ACT-FB01TX	ACT-FB01RX
	Optical fiber transmission	Fiber optic receiver
Input interface	1x BNC Connector 1x RS485 Connector	1x FC Type Fiber connectors
Output interface	FC Type Fiber connectors	1x BNC Connector 1x RS485 Connector
Video		
Interface	BNC	
Impedance	75ohm (unbalance)	
Frequency Range	1.0Vp-p	
Frequency bandwidth	50MHz	
Video resolution	1080P/720P/960H/D1	
Differential gain	<± 1% Type	
Differential phase (10%-90%,APL)	<± 1% Type	
SNR	>60dB(8Bit)	
Optical fiber	-28dBm	
Wavelength	1310nm & 1470nm-1610nm	
Fiber type	9/125u Single mode 50/125u Multi mode、62.5/125u Multi mode (Optional)	
Output Power	-3~-9dBm	
Receiver sensitivity	-26dBm	
Fiber optic connectors	FC, ST/SC(Optional)	
Power	110V~240V,DC5V,2A	
Operating temperature	-0℃ ~ 60℃	
Storage temperature	-20℃ ~ 70℃	
Working humidity	0~95% (Non-condensing)	