

ACT-FB02TXRX



Description Features:

- Support AHD/CVI/TVI/Analog all Signal
- Support resolution: 1080p, 720p, 960H,D1, all in one
- Compatible with NTSC、PAL、SECAM video formats automatically
- Supports RS485/Manchester Code/Diphase data, Switching signal
- FC Type, Single mode, Single fiber
- Compact structure, easily installation, plug and play
- Overpower protection and 5.7KV proof-lightning

Model No.	ACT-FB02TX	ACT-FB02RX
	Optical fiber transmission	Fiber optic receiver
Input interface	2 x BNC Connector 1x RS485 Connector	1x FC Type Fiber connectors
Output interface	FC Type Fiber connectors	2 x BNC Connector 1x RS485 Connector
Video		
Interface	BNC	
Impedance	75ohm (unbalance)	
Frequency Range	1.0Vp-p	
Frequency bandwidth	50MHz	
Video resolution	1080P/720P/960H/D1	
Differential gain	<± 1% Type	
Differential phase (10%-90%,APL)	<± 1% Type	
SNR	>60dB(8Bit)	
Optical fiber	-28dBm	
Wavelength	1310nm & 1470nm-1610nm	
Fiber type	9/125u Single mode 50/125u Multi mode、62.5/125u Multi mode (Optional)	
Output Power	-3~-9dBm	
Receiver sensitivity	-26dBm	
Fiber optic connectors	FC, ST/SC(Optional)	
Power	110V~240V,DC5V,2A	
Operating temperature	-0℃ ~ 60℃	
Storage temperature	-20℃ ~ 70℃	
Working humidity	0~95% (Non-condensing)	