

VCC-70ZH



Description Features:

- * 1/2.8" 2.1 Mega Pixel CMOS Image Processor
- * 20x Optical Zoom (4.7mm ~ 94.0mm Focal Range)
- * Simultaneous HD-SDI and Analog video output
- * SDI Video Outputs: HD-SDI
- * Analog Video Outputs: AHD, TVI, CVI, CVBS, EX-SDI
- * Durable aluminum camera housing

Model No.	VCC-70ZH
Image Sensor	1/2.8-Type Progressive Scan CMOS Image Sensor
Effective pixels	1945(H) x 1097(V)
Lens Type	20x optical zoom
Focal Length	Color : 0.1Lux (F1.2), B/W : 0.01Lux (F1.2)
Digital Wide Dynamic Range	4.7mm (wide) ~ 94.0 mm(tele)
Video Output Connectors	BNC Female x2
SDI Video Outputs	HD-SDI
SDI Video Standard	1080p: 30, 25 Hz / 720p: 60, 50, 30, 25Hz
Analog Video Outputs	AHD, TVI, CVI, CVBS, EX-SDI
Analog Video Standard	1080p: 30, 25 Hz / 720p: 60, 50, 30, 25Hz
Minimum Illumination	Color: 0.21Lux (F1.6) / B/W: 0.01Lux(F1.6)
S/N Ratio	48dB
Shutter Speed	1/50~1/100000 sec.
Focus Control	Auto Focus, Manual Focus
Digital Wide Dynamic Range	Support
Sens-up	x2 ~ x32
Day&Night Mode	Auto, Color, B&W, EXTERN
Backlight Compensation	OFF, HLC, BLC, WDR
White Balance	Auto, Manual
Dynamic Noise Reduction	Low, Middle, High
Flip / Mirror	BNC Female x2
Privacy Mask Image	OFF, ON
Gamma Correct	OFF, ON
Defog	OFF, ON
On Screen Display	English, T_Chinese, Japanese, Korean
Control Method	Screen Menu, Line Control
Control Interface	RS485
Control Protocols	Pelco-D
Baud rate	2400, 4800, 9600
Operating Temperature	-30°C ~ 60°C, Humidity 90% or less (non-condensing)
Storage Temperature	-30°C ~ 60°C
Power Supply	DC12V 1.0A
Dimensions / Weight	62(W) x 62(H) x 116(L)mm / 425g