

VCF-905



Features

- * Supports HDMI and SDI Signal input, and Analog audio input
- * Supports HDMI output and 2 channels SD/HD/3G-SDI output
- * Video scaling up/down conversion and frame rate conversion
- * Embedded Analog Audio
- * Automatically identify and configure HDMI/SDI input signal, easy control via DIP switches
- * Removable bracket design, suitable for wall-mounted installation
- * With USB for power supply

Specification	VCF-905		
Model	HDMI / SDI Signal Cross Converter		
Input Interface	HDMI Video Input	HDMI TypeA x 1	
	SDI Video Input	SD/HD/3G-SDI x 1	
	Analog Audio Input	1/8"(35mm) jack x 1	
Output Interface	HDMI Video Output	HDMI type A x 1	
	SDI Video Output	SD/HD/3G-SDI x 2	
Formats	SDI Input Format Support	1080p 60/59.94/50/30/29.97/25/24/23.98 1080Psf 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 625i 50.525i 59.94	
	SDI Video Rate	SD/HD/3G-SDI	
	SDI Compliance	SMPTE 292M, SMPTE 259M, SMPTE 424M	
	SDI Color Space and Precision	YUV4:2:2	
	HDMI Input Format Support	1080p 60/59.94/50/30/29.97/25/24/23.98/23.976 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 576p 50,576i 50 480i 60/59.94	
	HDMI Input Color Space and Precision	RGB 4:4:4 YUV 4:2:2 YUV 4:4:4	
	SDI HDMI Output Format Support	1080p 60/59.94/50/30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50	
	SIZE	Dimension(LWD)	125.5mm x 104mm x 24.5mm
		Wight	485g
	Power	Power Connector	Threaded Locking Connector Micro USB
Voltage Range		USB 3.3~5V DC 6~23V	
Power Consumption		4W	
Environment	Operating Temperature	-20°C~60°C	
	Storage Temperature	-30°C~70°C	
	Relative Humidity	0%~90% non-condensing	

Video Access Technology Corp.

6F.- 17, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
web : www.videoaccess.com

IP Surveillance Equipment
 HD-SDI / 3G-SDI Equipment
 AHD / TVI / CVI Equipment
 HDMI / VGA Equipment
 Speed Dome Camera
 Matrix Switcher Solutions