

AHD/CVI/TVI/CVBS to 3G-SDI/HDMI Converter

ACT-VF03



Description Features:

- * AHD/CVI/TVI/CVBS to 3G-SDI/HDMI
- * Support all type AHD/CVI/TVI/CVBS Video signal input
- * 3G-SDI output support : 1080p/1080i/720p 60_50Hz
- * HDMI output support 1080p/1080i/720P 60_50Hz
- * Output format: (3G-SDI and HDMI)
- * Easy to configure, and robust for 24/7 operation services

Specification	
Model No.	ACT-VF03
Connections	
AHD/TVI/CVI Video Inputs	1 x BNC -F
AHD/TVI/CVI Video Outputs	1 x loopout (BNC -F)
Input Signal Type	AHD / CVI / TVI / CVBS All Type
SDI Compliance	SMPTE425M(Level A and Level B) SMPTE424M SMPTE292M SMPTE259M-C and DVB-ASI
SDI Outputs	1 x SDI (without embedded audio)
SDI Rates	HD/3G-SDI
SDI Transmitting distance	Belden 1694A : 120m at 2.97Gb/s, 200m at 1.485Gb/s
HDMI Video Outputs	1 x TypeA (v1.4a)
Standards	
AHD/TVI/CVI Video Standards	720p30_25Hz 1080p30_25Hz 5MP / 4K
SDI Video Standards	720p 60_50Hz, 1080i 60_50Hz, 1080p 60_50Hz
SDI Color Precision	4:2:2
SDI Color Space	YUV
HDMI Video Standards	720p 60_50Hz 1920x1080i 60_50Hz 1920x1080p 60_50Hz
General	
Power Supply / Consumption	DC12V, 1A / 3.6 Watts
Operating Temperature	-10°C ~ 55°C
Storage Temperature	-30°C ~ 60°C
Relative Humidity	20 ~ 90% RH (Non-condensation)
Dimensions / Weight	145mm x 90mm x 35mm / 270g
Casing	Aluminum Case
Warranty	1-year warranty

Video Access Technology Corp.

6F.- 17, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
web : www.videoaccess.com