

VHDI-0120TX/RX



RECEIVER



Transmitter

Features:

- * Extend transmission distance is up to 120M via cat5/6
- * Support IR remote control to front Blu-ray, DVD ect by controlling the receiver end's IR control
- * LED indicator to show work status of PWR or data
- * Multipoint-to-multipoint mode support
- * RS232/EDID Support
- * HDMI signal loopout support
- * LPCM audio format support

Specification	VHDI-0120TX/RX	VHDI-0120TX/RX(P)
Transmitter	HDMI Type-A Female HDMI	
Input	Female port x1	
Output	RJ45 x1, HDMI Looping output	
RS232	RS232 Support	
IR	IR TX (38k ~ 56KHz), IR RX (38KHz)	
Receiver	1 x RJ45 Female	
Input	RJ45 x1	
Output	HDMI port x1	
RS232	RS232 Support	
IR	IR TX (38k-56KHz), IR RX (38KHz)	
POE Funtion	Not Support	Support
Video Compression	H.264	
Video Format	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Audio Format	Sample rate: 48kHz, LPCM	
IR remote control	38 ~ 56 KHz	
HDCP	Support	
RS232	2400, 4800, 9600, 19200 ~ 115200	
Default IP Address	TX:192.168.1.11 ; RX: 192.168.1.12	
Request for Switch/ Router	IGMP, DHCP Support	
Power consumption	HDMI Sender: 3W HDMI Receiver: 3W	
Dimensions / Weight	TX :120 x 80 x 28mm RX :120 x 80 x 28mm / 280g x2	
Storage Temperature/Humidity	-10℃ ~ 80℃, 5B ~ 90B RH (no condensation)	