

4 Channel HDMI ENCODER (H.265)

VMI-HN004-HD

Features

- HD Encoder with 4 x HDMI Inputs
- Encoding format: H.265/H.264/MJPEG
- Maximum resolution frame rate: 1920 x1080p
Low-latency private : 200 ms
- Video protocol: RTMP/RTSP/HTTP TS/HTTP FLV/HLS/UDP
multicast/RTP multicast
- Support ONVIF search and browse video docking with NVR
- Audio: HDMI audio input or 3.5mm external audio input,
supports stereo
- Configure parameters and upgrade firmware through WEB



Specifications	VMI-HN004-HD
Model No.	4 Channel HDMI ENCODER (H.265)
Video Input	VGA x 4
Video Output	VGA x 4
Video Encoding / Encoding type	H.264, H.265, M-JPEG Codec
Bitrate(Kbit)	Adjustable
HDMI Input Support	1080p 60, 59.94, 50Hz 1080i, 60, 59.94, 50Hz 720p, 60 50Hz
Video Compression Standard	High Profile, Main Profile
Streaming adjustments	CBR / VBR Adjustable
Media Transmission Protocols	RTMP, RTSP, TS, FLV, HLS, UDP Multicast, RTP Multicast
Audio Encoding	AAC, MP3, MP2, AC3 Adjustable
Audio encoding sample rate	44100 ~ 48000 Adjustable
Audio Video	AAC: 48000 ~ 320000 Adjustable
Audio bitrate	MP3: 64000 ~ 320000 Adjustable MP2: 64000 ~ 320000 Adjustable AC3: 40000 ~ 640000 Adjustable
Volume	Adjustable
Ethernet Port	100M
Network configuration	Web settings
ONVIF	Support
Power Supply	12VDC 2A
Power Consumption	5W
Operating Temperature	-20°C ~ 60°C, Humidity 90% or less (non-condensing)
Dimensions	480 x 200 x 45 mm
Weight	1830g

Video Access Technology Corp.

6F.-17, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone) Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com

BENESTON® | Data Sheet

videoaccess.com

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solution